

FEATURES

- Glass Passivated Die Construction
- Super-Fast Recovery Time For High Efficiency
- Low Forward Voltage Drop and High Current Capability
- Ideally Suited for Automated Assembly
- Plastic Material: UL Flammability Classification Rating 94V-0



SOD-123FL

MECHANICAL DATA

- Case: SOD-123FL Molded plastic
- Terminals: Pure tin plated, lead free
- Polarity: Indicated by cathode band
- Weight: 11.5 mg (approx.)



Cathode

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS







Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbol	ES2AL	ES2BL	ES2CL	ES2DL	ES2EL	ES2GL	ES2JL	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	150	200	300	400	600	V
Maximum RMS Voltage	V_{RMS}	35	70	105	140	210	280	420	V
Maximum DC Blocking Voltage	V_{DC}	50	100	150	200	300	400	600	V
Maximum Average Forward Rectified Current at $T_A = 75^\circ\text{C}$	$I_{F(AV)}$	2.0							A
Peak Forward Surge Current 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC)	I_{FSM}	50.0							A
Maximum Instantaneous Forward Voltage at 2 A	V_F	1				1.25	1.68		V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	5.0 50.0							μA
Maximum reverse recovery time (NOTE1)	t_{rr}	35.0							nS
Typical Junction Capacitance (NOTE2)	C_J	30.0							pF
Maximum Thermal Resistance (NOTE3)	$R_{\theta J}$ R_{ajc}	75 22							$^\circ\text{C/W}$
Operating and Storage Temperature Range	T_J, T_S	- 50 to + 150							$^\circ\text{C}$


Note: 1.Reverse recovery condition $I_F=0.5\text{A}$, $I_R=1.0\text{A}$, $I_{rr}=0.25\text{A}$

2.Measured at 1MHz and applied reverse voltage of 4.0V D.C.

3.P.C.B. mounted with 0.2x0.2"(5.0x5.0mm) copper pad areas

Typical Characteristics

SOD-123FL Package Outline Dimensions



UNIT		A	C	D	E	e	g	H _E	∠
mm	max	1.1	0.20	2.9	1.9	1.1	0.9	3.8	7°
	min	0.9	0.12	2.6	1.7	0.8	0.7	3.5	
mil	max	43	7.9	114	75	43	35	150	
	min	35	4.7	102	67	31	28	138	