


Distributeur : JBG-METAFIX

Features

- Box type provides the identical outer appearance.
- Wide capacitance range, small size.
- Long life due to self-healing effect.
- Suitable for block, by-pass and coupling of DC and signal to VHF range.
- Widely used in filter, noise suppression and low pulse circuits.



Configuration

Non-inductive, wound with metallized polyester film as dielectric and Electrode, copper-clad steel leads and encapsulated in a plastic case sealed with epoxy resin.

Specifications&Outline Drawing

Reference Standard	GB / T7332-1996	
Climatic Category	40/85/21	
Rated Voltage	100V, 160V, 250V, 400V, 630V	
Capacitance Range	0.010-10.0 μ F	
Capacitance Tolerance	$\pm 5\%$ (J), $\pm 10\%$ (K), $\pm 20\%$ (M)	
Voltage Proof	1.6U _R (5s)	
Dissipation Factor	$\leq 1.0\%$ (20℃, 1KHz)	
Insulation Resistance	$\geq 7500M\Omega$ (CR $\leq 0.33\mu$ F) $\geq 2500s$ (CR $> 0.33\mu$ F)	(20℃, 1min)


Dimensions

[illegible]

Distributeur : JBG-METAFIX

Features

- Box type provides the identical outer appearance.
- Wide capacitance range, small size.
- Long life due to self-healing effect.
- Suitable for block, by-pass and coupling of DC and signal to VHF range.
- Widely used in filter, noise suppression and low pulse circuits.



Configuration

Non-inductive, wound with metallized polyester film as dielectric and Electrode, copper-clad steel leads and encapsulated in a plastic case sealed with epoxy resin.

Specifications&Outline Drawing

Reference Standard	GB / T7332-1996	
Climatic Category	40/85/21	
Rated Voltage	100V, 160V, 250V, 400V, 630V	
Capacitance Range	0.010-10.0 μ F	
Capacitance Tolerance	$\pm 5\%$ (J), $\pm 10\%$ (K), $\pm 20\%$ (M)	
Voltage Proof	1.6U _R (5s)	
Dissipation Factor	$\leq 1.0\%$ (20℃, 1KHz)	
Insulation Resistance	$\geq 7500M\Omega$ (CR $\leq 0.33\mu$ F) $\geq 2500s$ (CR $> 0.33\mu$ F)	(20℃, 1min)

Dimensions

[illegible]